

## TECHNICAL DATA SHEET VIVWASH PLUS

Creation date 14/03/21  
Latest update 22/04/25  
Rev. 1

GENERAL INFORMATION		
A washable, highly opaque and velvety water paint with excellent coverage and intense white. It guarantees excellent brushability and flow, offering an extra matt finish thanks to the structured fillers in its formulation. Low emission		
TECHNICAL INFORMATIONS		
		NOTE
YIELD (50 dry $\mu\text{m}$ )	10-12 $\text{m}^2/\text{L}$	Theoretical
AVAILABLE DYES	White, colours on request	

TECHNOLOGICAL INFORMATIONS	
APPLICATIONS MODALITY	
BRUSH, ROLLER	Dil. 20-30% with DEMINERALIZED WATER
PAINTED WALLS	Brush off any residues of previous processes, dust and impurities. On absorbent supports, use a coat of <b>VIVFIX</b> beforehand. Proceed with the application of 2 or more coats of water-based paint, respecting application times, keeping the first coat of paint slightly (5%) thinner

DRYING	
DUST FREE	n/a
TOUCH FREE	30 min
DEEP DRYING	24 hours
Drying times can vary significantly depending on the thickness applied.	

## TECHNICAL DATA SHEET VIVWASH PLUS

Creation date 14/03/21  
Latest update 22/04/25  
Rev. 1

<b>OVERCOATING</b>
The product can be overpainted after 4-6 hours
<b>ENVIRONMENTAL CONDITION</b>
The substrate and outdoor temperature must be at least 3 degrees above the dew point.
<b>TOOLS CLEANING</b>
Tools can be cleaned of undried product with DEMINERALISED WATER.
<b>STORAGE</b>
In a cool and dry place, and in well sealed tin, the product is stable for at least 12 months. Storage temperature should be between 5°C and 35°C

The information given in this data sheet is indicative and based on our knowledge derived from experience and testing and can in no way constitute a guarantee. The purchaser/user is responsible for determining the suitability of the product for his or her own requirements in the context of the specific field of application. Please refer to the relevant toxicological data sheet for safety information.